



S.A.P.I.C.I. Spa  
 20063 Cernusco sul Naviglio (MI)  
 Via Bergamo, 2  
 Tel . (02) 921871  
 Fax (02) 92141949  
 www.sapici.it

# DATA SHEET

Issue date : 13/02/15  
 Last review date : 30/04/15  
 Edition N° : 1  
 Page : 1 of 1

## UCOPOL M 601

<b>Type of Polymer:</b>	Solventless polyurethane MDI based prepolymer.
<b>Range of use:</b>	Primer for concrete to be used for structural and corrosion protection.
<b>Specifications:</b>  (°) DATA SHOWN ON ANALYSIS CERTIFICATE	<b>UCOPOL M 601</b>  % NV 100 % NCO 23 ± 1 ° Viscosity (23°C mPa*s) 200 MAX °
<b>Application condition:</b>	UCOPOL M 601 can be used as impregnating agent with high reactivity, good levelling and wettability. It can be applied directly on cement screed. The humidity grade cannot exceed 5%. Its main function is to bind dust and moisture in order to strengthen the surface and create a better bond between the adhesive and the floor, reducing the working time.
<b>Storage and warranty:</b>	In sealed drums we guarantee a storage life of six months, provided UCOPOL M 601 is stored under dry and cool condition. Once opened, the drums should be used in short time, because UCOPOL M 601 is sensitive to moisture that can cause the curing of the product inside the drum.

The technical information provided in this sheet or given in oral or written form is based on our best knowledge and experience. These data, even technical and safety ones, are only suggestions, so they don't have to be considered as binding. The customer must test our products, technical assistance and information, to define to its satisfaction whether they are suitable for the intended use and application. The use, manufacture and the application conditions of our products are carried out beyond our control so they are under customer's responsibility. Sapici SpA guarantees the constant quality of the product, sales and delivery conditions.