

安鋒實業股份有限公司

台灣省台中市工業區 24 路 29 號 TEL:886-4-23501155 (代表) FAX:886-4-23507373
E-mail:anvictor@ms45.hinet.net 網站: www.twanfong.com

Solid acrylic resin AC-0554

Product properties:

Type	: BMA/MMA copolymer
Appearance	: white, clear, free flowing spherical beads
Solid content (%w/w)	: min 99 %
Tg (°C)	: 78
Average Mol. weight (Mw)	: 40000
Acid value	: 12
Viscosity (25°C; mPa.s)	: 250-400 (40% in Toluene)
Softening point	: 160
Density	: 1.15

Solubility and compatibility:

AC-0554 is soluble in ketones, aromatics and esters. Good compatible with NC, CAB, vinly's, chlorinated rubber and other acrylics.

Applications:

1. Plastic coatings and primer.
2. Marine and metal paints.
3. Car refinish paints.
4. Printing and screening inks.
5. Aerosols and ceramics.

End-use properties:

1. Tough, hard and resistant.
2. Broad compatibility.
3. High pigments soluble and flexible films.
4. Good adhesion and durability.

Storage:

Stored in a dry place, its shelf life is 2 years.

Remark :

This data is base on our current knowledge, it is correct and complete. However, it shall not constitute a guarantee for any specific product features. The customer is responsible to proof the data to be suitable for their own purposes.